

IN THE CLAIMS

1 1. (Original) A method for managing a code sequence, comprising:
2 processing a first set of sample values with coefficients from a first set of code sequence
3 coefficients to determine first partial accumulation results during a first time step;
4 processing a second set of sample values with coefficients from a second set of code
5 sequence coefficients to determine second partial accumulation results during a second time step;
6 processing the second set of sample values with coefficients from the first and second set
7 of code sequence coefficients to determine third partial accumulation results during the second
8 time step;
9 generating a lag result for a first sequence of sample values in response to the first and
10 second partial accumulation results; and
11 generating a lag result for a second sequence of sample values in response to the first and
12 third partial accumulation results.

1 2. (Currently Amended) The method of Claim 1, further comprising:
2 processing a third set of sample values with coefficients from a third set of code
3 sequence coefficients to determine fourth partial accumulation results during a ~~fourth~~third time
4 step; and
5 updating the lag result for the second sequence of sample values in response to the first,
6 third, and fourth partial accumulation results.

1 3. (Original) The method of Claim 1, further comprising determining a synchronization
2 point for the code sequence from the lag results for the first and second sequence of sample
3 values.

1 4. (Currently Amended) The method of Claim 3, wherein determining a synchronization
2 point comprises determining a lag result from the first and second sequences of sample values
3 having the highest numerical value.

1 5. (Original) The method of Claim 1, wherein the first and second set of code sequence
2 coefficients are contiguous coefficients from the code sequence.

1 6. (Original) The method of Claim 1, wherein the first and second set of sample values
2 are contiguous sample values in a received sample.

1 7. (Currently Amended) The method of Claim 1, wherein ~~generating~~to determine first
2 partial accumulation results from at the first set of sample values and coefficients from at the first
3 set of code sequence coefficients during at the first time step comprises taking the products of the
4 first set of sample values and the coefficients from the first set of code sequence coefficients.

1 8. (Original) The method of Claim 1, wherein generating the lag result for the first
2 sequence of sample values in response to the first and second partial accumulation results
3 comprises taking a sum of the first and second partial accumulation results.

1 9. (Currently Amended) A method for managing a code sequence, comprising:
2 accessing a first set of n coefficients in the code sequence and a first set of n sample
3 values in a first sample sequence during a first time step;
4 processing the first set of n sample values with coefficients in the first set of n
5 coefficients to determine first partial accumulation results;
6 accessing a second set of n coefficients in the code sequence and a second set of n
7 sample values in the first sample sequence during a second time step;

8 processing the second set of n sample values with coefficients in the second set of n
9 coefficients to determine second partial accumulation results; and
10 generating a lag result for athe first sample sequence from the first and second partial
11 accumulation results.

1 10. (Original) The method of Claim 9, further comprising:
2 processing the second set of n sample values with coefficients in the first and second set
3 of n coefficients to determine third partial accumulation results; and
4 generating a lag result for a second sample sequence from the first and third partial
5 accumulation results.

1 11. (Original) The method of Claim 10, further comprising:
2 accessing a third set of n sample values in the sample during a third time step;
3 processing the third set of n sample values with coefficients in the second set of n
4 coefficients to determine fourth partial accumulation results; and
5 updating the lag result for the second sample sequence with the fourth partial
6 accumulation results.

1 12. (Original) The method of Claim 9, wherein the first and second set of n coefficients
2 are contiguous code sequence values in the code sequence.

1 13. (Original) The method of Claim 9, wherein the first and second set of n sample
2 values are contiguous sample values in the sample.

1 14. (Original) The method of Claim 9, wherein processing the first set of n sample
2 values with coefficients in the first set of n coefficients to determine the first partial

3 accumulation results comprises taking the products of the first set of n sample values and the
4 coefficients in the first set of n coefficients.

1 15. (Currently Amended) The method of Claim 9, wherein ~~determining~~generating the
2 lag result for the first sample sequence from the first and second partial accumulation results
3 comprises taking a sum of the first and second partial accumulation results.

1 16. (Currently Amended) A method for managing a code sequence, comprising:
2 accessing sets of n contiguous sample values that include sample values in a plurality of
3 sample sequences;
4 accessing sets of n contiguous coefficients; and
5 processing in parallel the sample values in each of the plurality of sets of sample values
6 that are accessed ~~in parallel~~ with corresponding coefficients that are accessed, where each of the
7 plurality of sets of sample values are processed during a different time step.

1 17. (Original) The method of Claim 16 further comprising generating lag results for
2 each of the sample sequences.

1 18. (Original) The method of Claim 16, wherein each of the sets of n contiguous sample
2 values is accessed at a different time step.

1 19. (Original) The method of Claim 16, wherein each of the sets of n contiguous
2 coefficients is accessed at a different time step.

1 20. (Original) The method of Claim 16, wherein processing the sample values in each
2 of the plurality of sets of sample values with corresponding coefficients comprises generating
3 partial accumulation results.

1 21. (Currently Amended) A correlator unit, comprising:
2 a plurality of n sample sequence registers that store sample values from a plurality of
3 sample sequences that are processed in parallel, the plurality of n sample sequence registers
4 storing sample values from one set of sample values of a plurality of sets of sample values from
5 the plurality of sample sequences at a time;
6 a plurality of $2n$ code sequence registers that store up to $2n$ coefficients from a code
7 sequence; and
8 a processing unit that processes the sample values in each of the plurality of sets of
9 sample values in the plurality of n sample sequence registers in parallel with corresponding
10 coefficients in the plurality of $2n$ code sequence registers, where each of the plurality of sets of
11 sample values is processed during a different time step.

1 22. (Original) The correlator unit of Claim 21, wherein the processing unit comprises
2 an addition-multiplication tree.

1 23. (Original) The correlator unit of Claim 22, wherein the addition-multiplication tree
2 comprises:
3 a plurality of specialized multiplexers; and
4 a plurality of adders.

1 24. (Original) The correlator unit of Claim 23, wherein each of the specialized
2 multiplexers, comprises:

- 3 a multiplexer; and
- 4 a plurality of circuits that perform an XOR function.